

DIN-Signal coax f, solder/crimp, 500hm



Part number	09 03 000 6260
Specification	DIN-Signal coax f, solder/crimp, 500hm
HARTING eCatalogue	https://b2b.harting.com/09030006260

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Contacts
Series	DIN 41612
Type of contact	Coaxial contact
Description of the contact	Straight
Contacts for	DIN 41612 Type M DIN 41612 Type M invers DIN 41612 Type MH 21+5 DIN 41612 Bauform M 0+2 har-modular® M module, male, angled har-modular® M module, male, straight

Version

Termination method	Solder/crimp termination
Gender	Female contact for male connectors
Manufacturing process	Turned contacts

Technical characteristics

Operating current	≤1.4 A
Rated voltage	250 V
Insulation resistance	>10 ⁹ Ω
Contact resistance	≤10 mΩ for inner contact die
	≤3 mΩ for outer ferrule
Impedance	≤3 m Ω for outer ferrule 50 Ω



Technical characteristics

Return loss	>19 dB @ 1 GHz for cables RG 316 >15 dB @ 2 GHz for cables RG 316
Insertion force	≤10 N
Withdrawal force	≥1 N
Performance level	1
Mating cycles	≥500
Test voltage U _{r.m.s.}	0.75 kV
Frequency	2 GHz

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni Mating side
Material (locking)	Copper alloy
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	339476a1-86ba-49e9-ab4b-cd336420d72a
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead

Specifications and approvals

|--|

Commercial data

Packaging size	100
Net weight	2.041 g
Country of origin	Germany
European customs tariff number	85366990




Commercial data

eCl@ss

27440204 Contact for industrial connectors

Assembly instructions



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING: 09030006260