



N=Number of contacts



PCB LAYOUT - COMPONENT VIEW

TECHNICAL CHARACTERISTICS

MATERIAL
INSULATOR: PBT
FLAMABILITY RATING: UL94-V0
COLOR: GREEN
CONTACT: BRASS
SOLDER TAIL PLATING: TIN

ENVIRONMENTAL
OPERATING TEMPERATURE: -40 UP TO 105°C
COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
CURRENT RATING: 20A
WORKING VOLTAGE: 300VAC
WITHSTANDING VOLTAGE: 1.6KV
CONTACT RESISTANCE: 20 mOhm max

MECHANICAL
PITCH: 7.62MM



SOLDERING: WAVE PROCESS ONLY

PACKAGING: BOX

SERIE 3114

CERTIFICATION



RoHS Compliant				<div>PROJECTION:</div> <div></div>	<div>GENERAL TOLERANCE</div> <div>.X = \pm 0.2</div> <div>.XX = \pm 0.15</div>	<div></div> <div>WÜRTH ELEKTRONIK</div>		D	
G									
F									
E									
D				APPROVAL: RJ	UNIT: MM	DESCRIPTION: SERIE 3114 - 7.62MM CLOSE VERTICAL PCB HEADER WR-TBL	SIZE A4		
C					SCALE:				
B					SHEET: 1/1				WERI PART NO: 691 311 400 1xx
A	12-NOV-08	PDF	JP		DRAW: MARVIN				
REV	DATE	FILE	BY						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Würth Elektronik:](#)

[691311400106](#)