

## Y distributor - SAC-5P-M12YF/M12FS-M12MS VP - 1526253

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid  
(<http://phoenixcontact.com/download>)



Y distributor, 5-position, Socket straight M12, coding: A, on Socket straight M12, coding: A and Plug straight M12, coding: A, Parallel distributor

RoHS

### Key Commercial Data

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Packing unit | 5 pc                                                                                 |
| GTIN         |  |
| GTIN         | 4017918954291                                                                        |

### Technical data

#### Dimensions

|                 |       |
|-----------------|-------|
| Center distance | 18 mm |
|-----------------|-------|

#### Ambient conditions

|                      |      |
|----------------------|------|
| Degree of protection | IP65 |
|                      | IP67 |

#### General

|                             |                               |
|-----------------------------|-------------------------------|
| Rated current at 40°C       | 4 A                           |
| Rated voltage               | 48 V AC                       |
|                             | 60 V DC                       |
| Number of positions         | 5                             |
| Insulation resistance       | ≥ 100 MΩ                      |
| Coding                      | A - standard                  |
| Standards/regulations       | M12 connector IEC 61076-2-101 |
| Status display              | No                            |
| Overvoltage category        | II                            |
| Degree of pollution         | 3                             |
| Insertion/withdrawal cycles | ≥ 100                         |
| Torque                      | 0.4 Nm (M12 connector)        |

## Y distributor - SAC-5P-M12YF/M12FS-M12MS VP - 1526253

### Technical data

#### Material

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | HB                                          |
| Contact material                       | CuZn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Material, knurls                       | Zinc die-cast, nickel-plated                |
| Sealing material                       | NBR                                         |

#### Standards and Regulations


|                                        |                               |
|----------------------------------------|-------------------------------|
| Standards/specifications               | M12 connector IEC 61076-2-101 |
| Flammability rating according to UL 94 | HB                            |

#### Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

### Drawings


Dimensional drawing



Plug M12 x 1, Y distributor

## Y distributor - SAC-5P-M12YF/M12FS-M12MS VP - 1526253


Circuit diagram



Contact assignment of the M12 Y distributor

## Y distributor - SAC-5P-M12YF/M12FS-M12MS VP - 1526253


Schematic diagram



Pin assignment M12 male connector, 5-pos., A-coded, male side


## Y distributor - SAC-5P-M12YF/M12FS-M12MS VP - 1526253

Schematic diagram



Pin assignment M12 socket, 5-pos., A-coded, socket side view

Schematic diagram



Layout of connector pin assignments

## Y distributor - SAC-5P-M12YF/M12FS-M12MS VP - 1526253

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27440106 |
| eCl@ss 4.0    | 27060300 |
| eCl@ss 4.1    | 27060300 |
| eCl@ss 5.0    | 27061800 |
| eCl@ss 5.1    | 27061800 |
| eCl@ss 6.0    | 27279200 |
| eCl@ss 7.0    | 27440104 |
| eCl@ss 8.0    | 27440104 |
| eCl@ss 9.0    | 27440106 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000830 |
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC002062 |
| ETIM 6.0 | EC002925 |
| ETIM 7.0 | EC002925 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |
| UNSPSC 19.0   | 31251501 |
| UNSPSC 20.0   | 31251501 |
| UNSPSC 21.0   | 31251501 |

### Approvals

#### Approvals

---

##### Approvals

UL Listed / cUL Listed / EAC / EAC / cULus Listed

---

##### Ex Approvals

---

#### Approval details

## Y distributor - SAC-5P-M12YF/M12FS-M12MS VP - 1526253

### Approvals

|                    |                                                                                   |                                                                                                                                                       |         |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| UL Listed          |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E221474 |
|                    |                                                                                   |                                                                                                                                                       |         |
| Nominal voltage UN |                                                                                   | 30 V                                                                                                                                                  |         |
| Nominal current IN |                                                                                   | 4 A                                                                                                                                                   |         |

|                    |                                                                                   |                                                                                                                                                       |         |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| cUL Listed         |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E221474 |
|                    |                                                                                   |                                                                                                                                                       |         |
| Nominal voltage UN |                                                                                   | 30 V                                                                                                                                                  |         |
| Nominal current IN |                                                                                   | 4 A                                                                                                                                                   |         |

|     |                                                                                    |               |
|-----|------------------------------------------------------------------------------------|---------------|
| EAC |  | EAC-Zulassung |
|-----|------------------------------------------------------------------------------------|---------------|

|     |                                                                                     |                          |
|-----|-------------------------------------------------------------------------------------|--------------------------|
| EAC |  | RU C-<br>DE.BL08.B.00511 |
|-----|-------------------------------------------------------------------------------------|--------------------------|

|              |                                                                                     |
|--------------|-------------------------------------------------------------------------------------|
| cULus Listed |  |
|--------------|-------------------------------------------------------------------------------------|

### Accessories

#### Accessories

#### Plug for cable screw gland

Screw plug - PROT-M12 - 1680539



An M12 screw plug for the unoccupied M12 sockets of the sensor/actuator cable, boxes and flush-type connectors

## Y distributor - SAC-5P-M12YF/M12FS-M12MS VP - 1526253

### Accessories

Screw plug - PROT-M12 MS-PA-CHAIN - 1430899

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



---

### Protective cap

Sealing cap - PROT-M12 FS - 1560251



M12 sealing cap for unoccupied M12 plugs of the sensor/actuator cable, flush-type plugs and I/O devices in the field

---

Sealing cap - PROT-M12 FS-PA-CHAIN - 1430873

M12 sealing cap made of plastic with fixing band, for sensor cables, for free M12 plugs



---

### Screwdriver tools

Tool - SAC BIT M12-D15 - 1208432



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

---

### Torque tool

Torque screwdriver - TSD 04 SAC - 1208429



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors



Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1526253](#)