



Suitable for use with Storm USB Keypad Encoder (4500-00)



3000 Series Part Numbers

	F key format	3K04210
	Arrow key format	3K04110
	Telephone format	3K12T10
	Calculator format	3K12010
	Telephone format	3K16T10
	Calculator format	3K16010



Electrical

Contact Bounce	5ms (max)
Contact Resistance	100 ohms (max)
Insulation Resistance	50 Mohms (min)
Breakdown Voltage	500V AC (max 60 secs.)
Operating Voltage	24V DC (max)
Operating Current	50mA (max)

Mechanical

Operational Life	2 million cycles (min) per key
Keytop Travel	1.4mm nominal
Actuation Force	180gms nominal
Connector	0.1" pitch, gold plated square pin, male connector

Environmental

Water / Dust Sealed	IP54 (when fixed to a suitable enclosure)
Operational Temperature	-10°C to +85°C (Dry)

Material

Casing	General Service Polymer (black)
Keytops	General Service Polymer (translucent)
Contact Circuit	Gold on Nickel Plated FR4



For more information & to order:

www.storm-interface.com



Whilst every effort is made to ensure details are correct at time of print, specifications are subject to change without notice.

Designed & produced by NIK Design
nik@nikdesign.co.uk

Storm Interface products include technology protected by international patents and design registration. All rights reserved.

Storm is a trademark of Keymat Technology Ltd
Storm Interface is a trading name of Keymat Technology Ltd



3K August 2013

FM 39602



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Storm Interface:

[3K041103](#) [3K042103](#) [3K120103](#) [3K12T103](#) [3K160103](#) [3K16T103](#)