


JKL PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF22180-28B	x = .346 y = .319	1140 @ 0°C	380	5 ± 1	38,000 ±10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<div>METRIC</div> <div></div> <div>THIRD ANGLE PROJECTION</div>		<div>DIMENSIONS ARE IN MILLIMETERS</div> <div>TOLERANCE UNLESS OTHERWISE SPECIFIED</div> <div>1 PL +/- 0.2</div> <div>2 PL +/- 0</div> <div>ANGLE +/- 0</div>		<div>JKL COMPONENTS CORPORATION</div> <div>TITLE</div> <div>MINIATURE COLD CATHODE FLUORESCENT LAMP</div>				
B	RATED LIFE HRS MINIMUM	7/30/09	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING NO.	BF22180-28B		
A	CIRCUIT & LAMP VOLTAGE CHANGE	7/19/04	L. WENGSTROM	L.R.	7/30/09	A	55335				
	RELEASED & CANCEL P-0303-14	9/2/03									
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET	
						NONE	9/2/03	7/30/09	B	1 OF 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[JKL Components:](#)

[BF22180-28B](#)