

SIEMENS

Product data sheet

3RT1526-1BB40


CONTACTOR, AC-3, 11KW/400V, DC 24 V,
4-POLE, 2 NO + 2 NC, SIZE S0,
SCREW CONNECTION

Abb. ähnlich / similar picture

General details:

Size of the contactor	S0
Number of poles	4

Control circuit:

Design of activation of the operating mechanism	conventional
Type of voltage	DC
Control supply voltage	
• for DC / rated value / minimum	24 V
• for DC / rated value / maximum	24 V

Main circuit:

Number of NC contacts / for main contacts	2
Number of NO contacts / for main contacts	2
Operating current	
• at AC-3 / at 400 V / rated value	20 A
• at AC-1 / at 400 V / rated value	40 A
Service power	
• at AC-3 / at 400 V / rated value	11 kW
• at AC-1 / at 400 V / rated value	26 kW

Auxiliary circuit:

Number of NO contacts / for auxiliary contact	0
Number of NC contacts / for auxiliary contact	0
Connection type:	
Design of the electrical connection / for main current circuit	screw-type terminals
Design of the electrical connection / for auxiliary and control current circuit	screw-type terminals
Mounting/fixing:	
Type of fixing/fixation	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Series installation	Yes

last change: 10/31/2006

Technical Assistance:	Telephone:	+49 (0) 911-895-5900 (8°° - 17°° CET)
	Fax:	+49 (0) 911-895-5907
	E-Mail:	technical-assistance@siemens.com
	Internet:	www.siemens.de/lowvoltage/technical-assistance